

BLUESIL RTV 3040 A U1

Description

Bluesil™ RTV 3040 is a clear, high strength, addition cure silicone rubber compound. It is formulated to be used with multiple catalysts to cure overnight at room temperature or within hours at elevated temperature to give a variety of hardness. Its low viscosity makes the product easy to pour and quick to degas.

Bluesil™ RTV 3040 is designed to serve the needs of the prototyper by reproducing intricate details and maintaining tight tolerances. In addition, **Bluesil™ RTV 3040** has been formulated to provide improved urethane resin resistance.

- Examples of applications**
- Conventional production and prototype molds
 - Finished rubber parts
 - Stereolithography (SLA) molds

Key benefits Please consult your local ELKEM SILICONES sales office.

Typical properties

Typical Properties	
<p>TYPICAL PROPERTIES – AS SUPPLIED</p> <p><u>Part A – Base Component</u></p> <ul style="list-style-type: none"> • Appearance Clear to Straw Yellow • Consistency Pourable • Viscosity, Cp. (mPa.s) 50,000 <p>Part B – Catalyst Component</p> <ul style="list-style-type: none"> • Color Translucent 	<p>TYPICAL CATALYZED PROPERTIES</p> <p>Mixed at 24°C (75°F) and 50% R.H.</p> <ul style="list-style-type: none"> • Mixed Ratio, A:B (Parts by weight) 10:1 • Viscosity, cP.(mPa.s) 40,000

TYPICAL PROPERTIES OF CURED RUBBER, Cured 24 hours at 24°C (75°F) and 50% R.H.

Property	Test Method	CATA 3038	CATA 3040	CATA 3045
Appearance		Clear to Straw Yellow		
Specific Gravity		1.08		
Work Life, hours (1)		1	1	1
Pot Life, hours (2)		2	2	2
Hardness (Shore A)	ASTM D2240	36	38	45
Tensile Strength, psi (n/mm ²)	ASTM D412	900 (6.2)	920 (6.3)	915 (6.2)
Elongation (%)	ASTM D412	340	340	205
Tear Resistance, ppi (n/mm)	ASTM D624, Die B	100 (17.5)	120 (21)	130 (23)
Linear Shrinkage(3) (%) 24 Hours		< 0.1		
7 Days		< 0.1		
Temperature Range °C (°F)		-54 to 204 (-65 to 400)		

BLUESIL RTV 3040 A U1

NOTE: Cure may be accelerated by curing at 40-65°C (120-150°F) for 3-4 hours. HEAT CURING MAY INCREASE SHRINKAGE.

1. Time required to double initial catalysed viscosity (3) 8x8x0.25 in (20.3x20.3x0.64 cm) molded sheet, cured at room temperature
2. Time at which material gels NOTE: Cure at elevated temperatures may cause modification of rubber properties and increase shrinkage Please note: The typical properties listed in this bulletin are not intended for use in preparing specifications for any particular application of **Bluesil™** silicone materials. Please contact our Technical Service Department for assistance in writing specifications.

Please note: The typical properties are not intended for use in preparing specifications. Please contact our local Sales Department for assistance in writing specifications.

Instruction of use

1. Stir the base (Part A) well before use (except when machine dispensing)
2. Shake the catalyst container (Part B) well before use.
3. Weigh the desired amount of base into a clean mixing container. Tip the container and roll the base all the way around the side wall up to two inches from the top. This will prevent the catalyst from becoming absorbed into the container. It is recommended that the container be filled to not more than 1/3 the container depth to allow sufficient room for expansion during the deaeration procedure.
4. Weigh the proper amount of catalyst into the container. Mix the base and catalyst together by stirring with a stiff, flat ended metal spatula until a uniform color is obtained. Scrape the container walls and bottom well to insure a thorough mix.
5. Place the container into a vacuum chamber and evacuate the entrapped air from the mixture using a vacuum pump capable of achieving 29 inches of mercury vacuum. The mixture will rise, crest and then collapse in the container. Interruption (bumping) of the vacuum may be necessary to prevent overflowing the container. Keep the mixture under full vacuum for 2-3 minutes after the material has receded in the container.
6. Bleed air slowly into the vacuum chamber. When the chamber is at atmospheric equilibrium, remove the cover plate and take out the container.
7. Pour the desired material slowly in a steady stream from one end of the mold box so that the material flows evenly over the pattern. This should minimize entrapment of air bubbles under the flowing material. A "print" coat may be poured first over the pattern which will also help reduce the possibility of entrapping air on the pattern and in the cured rubber. A mold release (petroleum jelly) may be applied on the pattern first to improve release.
8. Allow the rubber to cure for 16-24 hours at 75±5°F (24°C) before removing the cured rubber mold from the pattern. For best results, allow the mold to air cure an additional 24 hours before using it in production. Full cure is achieved in 3-7 days

MIXED PROCESSING PROPERTIES WILL BE AFFECTED BY TEMPERATURE VARIATIONS

- A decrease in work life and pot life may be expected to occur at temperatures exceeding 75°F (24°C). Room temperature curing moldmaking rubbers are particularly sensitive to higher temperatures. Refrigeration of the base (Part A) prior to use in hot environments has shown to improve the handling properties of these materials.
- Lower temperatures will increase the work life and pot life of this material. Cure temperatures below 68°F (20°C) are not recommended, and have been found to cause a reduction in final cure hardness and physical properties.

This system contains a platinum CATALYST, which may be inhibited by materials found in some organic polymer systems, chlorinated solvents, and some substrates. Especially troublesome materials are: amine cured epoxies, sulfur cured organic rubber systems such as natural rubber, polysulfide rubber, latex rubber and adhesives, sulfur containing modeling clays, PVC coated surfaces, and tin catalyzed silicone RTV rubbers. A patch test to determine compatibility is recommended when doubts exists.

BLUESIL RTV 3040 A U1

Regulation	Please consult your local ELKEM SILICONES sales office.
Limitations	Please consult your local ELKEM SILICONES sales office.
Packaging	<ul style="list-style-type: none">• BLUESIL RTV 3040 A U1 is available in<ul style="list-style-type: none">○ Drum of 200 KG (441 LB)○ Pail of 20 KG (44.1 LB)○ Piece of 1 PC
Storage and shelf life	When stored in its original packaging: BLUESIL RTV 3040 A U1 may be stored for up to 18 months from its date of manufacturing. Comply with the storage instructions and expiration date marked on the packaging. Beyond this date, Elkem Silicones no longer guarantees that the product meets the sales specifications.
Safety	Please consult the Safety Data Sheet of: BLUESIL RTV 3040 A U1

Visit our website www.elkem.com/silicones/

Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELKEM SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Determination of the suitability of product for the uses and applications contemplated by users and others shall be the sole responsibility of users. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELKEM SILICONES is at their disposal to supply any additional information.